

LITHIUM-ION BATTERY DATASHEET

AVAILABLE IN:

240 Ah
12V



MORE POWER IN LESS SPACE

The Xantrex Lithium-Ion Iron Phosphate (LiFePO₄) Battery uses UL1973¹ certified cells. Equipped with redundant safety features, the Xantrex Lithium-Ion Battery is the safest in the market today. Specifically designed to withstand the harsh operating environments of mobile applications, the Xantrex Lithium-Ion Battery lasts up to 6,000 cycles² compared to a traditional lead acid or AGM battery, which typically lasts 400–500 cycles. The Xantrex Lithium-Ion Battery offers exceptional power density and is also available with a heating blanket option if installation is outside the main cabin.



Internal BMS - reduces footprint



Cell Balancing - extends lifetime of battery



LED's to monitor State of Charge



Remote Panel - view status of battery, turn battery on and off



Connect to the Xantrex mobile app to view status of battery



Parallel stack up to 4 batteries

APPLICATIONS:



**10 YEAR
WARRANTY³**

www.xantrex.com
CUSTOMER CARE: 1.800.670.0707


Copyright © 2023 Xantrex LLC. All Rights Reserved. All trademarks are owned by Xantrex LLC.

V5. 10.25.2023

¹(File MH62898; Model 6LH3L7)

²Up to 6,000 cycles under ideal conditions


³Refer to our warranty policy document for full warranty details




AVAILABLE NOW
XANTREX APP

- Connect via smartphone
- Monitor battery


DOWNLOAD ON



12V 240AH DIMENSIONS



PARALLEL STACK UP TO 4 BATTERIES



BATTERY SPECIFICATIONS

Part Number	883-0240-12
Battery Voltage	12 V
Nominal True Capacity	240 Ah
Nominal Voltage	12.8 V
Nominal Watt Hours	3072 Wh
Internal Impedence	< 4 mΩ
Charge Voltage	14.6 V
Recommended Float Charge Voltage	13.6 V
Recommended Charge Current	≤ 100 A
Allowed Max Charge Current	150 A
Output Voltage Range	10.0–14.6 V
Recommended Discharge Current	100 A
Max Continuous Discharge Current	150 A
Pulse Discharge Current	300 A (3 s)
Discharge Cut-off Voltage	10 V

ENVIRONMENTAL

Charging Temperature Range	32–131°F (0–60°C)
Discharging Temperature Range	-4–131°F (-20–60°C)
Storage Period 1 Week	-4–113°F (-20–45°C)
Storage Period 1 Month	14–113°F (-10–45°C)
Storage Period 6 Months	50–77°F (10–25°C)

MECHANICAL

Dimensions	19.7 x 7.1 x 10.3" (500 x 180 x 260 mm)
Weight	69.4 lb (31.5 kg)
Battery Terminals	M8 x 1.25
Carrying Capability	Two metal handles
Mounting Orientation	Standing or On Its Side

CERTIFICATION

U.N. International Approval	UN/DOT 38.3 Lithium Ion
UL1973 Certified Cells	File MH62898; Model 6LH3L7

CONTACT

CUSTOMER SERVICE

1.800.670.0707
 customerservice@xantrex.com
 Hours of operation:
 6:30am - 4:30pm PST, Monday to Friday

 [facebook.com/Xantrex](https://www.facebook.com/Xantrex)

 @Xantrex

 [youtube.com/XantrexTechnology](https://www.youtube.com/XantrexTechnology)

LEARN MORE ON:

www.xantrex.com