

PROwatt 250 & 800

INVERTER

xantrex™
Smart choice for power™

Provides portable AC power

Available in:

24 V



Prowatt 800

The PROwatt 250 plugs into the lighter socket of your vehicle, boat or RV to provide 250 watts of continuous power suitable for a range of appliances, electronics and power tools including VCRs, stereos, TVs up to 25" and laptop computers. The exact run time depends on the amount of power being drawn by the application. PROwatt 250 can surge up to 500 watts to handle equipment that requires more power.

A mid-range inverter designed for industrial and recreational applications, the Prowatt 800 is ideal for heavy-duty AC loads or smaller, multiple AC loads. Common applications include microwaves, TV/VCRs and a variety of small power tools.

Product Features

- » Regulated output frequency for time sensitive applications (Prowatt 250)
- » Auto shutdown prevents total battery discharge (Prowatt 250)
- » Compact size for convenient use and storage (Prowatt 250)
- » Dual GFCI outlet for safer operation (Prowatt 800)
- » Supports addition of external AC outlets (Prowatt 800)
- » Built-in LED display for DC volts and amps (Prowatt 800)
- » Includes remote on/off switch (Prowatt 800)
- » Silent operation (all)
- » One year warranty (all)

Protection Features

- » Low voltage shutdown
- » Overload shutdown
- » Over temperature shutdown
- » Over and under voltage protection
- » Low voltage alarm

Applications:



Recreational vehicles



Marine



Heavy duty trucks



Work vehicles



Buses / coaches



Specialty vehicles



ETL listed to CSA Standard C22.2 No. 107.1 and UL 458* with Marine supplement

*For marine supplement compliance drip shield in specific mounting orientation is required. See installation guide



Schneider Electric Solar Business

3700 Gilmore Way
Burnaby, British Columbia
Canada V5A 4B5
800 670 0707 Toll Free
604 420 1591 Fax

541 Roske Drive, Suite A
Elkhart, Indiana
USA 46516
800 446 6180 Toll Free
574 294 5989 Fax

www.xantrex.com

PROwatt 250 & 800

INVERTER



Electrical specifications	250	800
Max. continuous AC power	250 watts	800 watts
Surge capacity (peak)	500 watts	2000 watts
AC output frequency	60 +/- 0.05 Hz, crystal controlled	60 +/- 4 Hz
AC output voltage	115 VAC RMS +/- 10%	115 VAC RMS +/- 5%
Output waveform	Modified sine wave	Modified sine wave
Peak efficiency	90%	90%
No load current draw	< 0.1 A	< 0.3 A
Input voltage range	20-30 VDC	20-30 VDC

General specifications		
Output temperature range	32°F – 104°F / 0°C – 40°C	32°F – 104°F / 0°C – 40°C
AC receptacle	3-prong	Dual GFCI
DC connection	DC socket	Hardwire
Internal fuse	30 A	Internal, not user replaceable
LED display	N/A	DC Volts & Amps
Dimensions (H x W x L)	1.5 x 4.5 x 6.0" (38 x 115 x 115 mm)	3.25 x 9.5 x 10.25" (80 x 240 x 260 mm)
Weight	26 oz (740 g)	5.8 lb (2.6 kg)
Warranty	Two year	Two year
Part number	801-3255	801-3853 808-9000 (remote switch)

Note: Specifications subject to change without notice.